We claim:

 $\begin{pmatrix} 1 \\ 2 \\ 3 \end{pmatrix}$

4 5

6

7

8

9

A method for determining crystallization conditions for a material, the method comprising:

taking a plurality of different crystallization samples in an enclosed microvolume, the plurality of crystallization samples comprising a material to be crystallized and crystallization conditions which vary among the plurality of crystallization samples;

allowing crystals of the material to form in plurality of crystallization samples; and

identifying which of the plurality of crystallization samples form crystals

- 1 2. The method according to claim 1 wherein the material to be crystallized is 2 a macromolecule.
- 1 3. The method according to claim 1 wherein the material to be crystallized is a protein.
- 1 4. The method according to claim 1 wherein the material to be crystallized is a 2 macromolecule with a molecular weight of at least 500 daltons.
- 1 5. A method according to claim 1 wherein the material to be crystallized is
- 2 selected from the group consisting of viruses, proteins, peptides, nucleosides,
- 3 nucleotides, ribonucleic acids, de xyribonucleic acids.

300 1

6. A method according to claim 1 wherein the material to be crystallized is selected from the group consisting of viruses, proteins, peptides, nucleosides, nucleotides, ribonucleic acids, deoxyribonucleic acids.

1 2. A method according to claim 1 wherein the enclosed microvolume is a lumen.

1	A method according to claim 1 wherein the enclosed microvolume is a
2	lumen with a cross sectional diameter of less than 2.5 mm.
	્ય
1	9. A method according to claim 1 wherein the enclosed microvolume is a
2	lumen with a cross sectional diameter of less than 1 mm.
1	S 10. A method according to claim 1 wherein the enclosed microvolume is a
2	lumen with a cross sectional diameter of less than 500 microns.
1	A method according to claim 1 wherein the enclosed microvolume is a
2	microchamber.
	1
1)2. A method according to claim 1 wherein the enclosed microvolume is at
2	least partially enclosed within a substrate which comprises other enclosed
3	microvolumes which also comprise crystallization samples.
_	<u>\$</u>
1	13. A method according to claim 1 wherein the enclosed microvolume is at
2	least partially enclosed within a card shaped substrate.
1	14. A method according to claim 1, the method further comprising performing
2	a spectroscopic analysis on a crystal formed within a microvolume within the
> 3	microvolume.
1	15. A method according to claim 14, wherein the spectroscopic analysis is
2	selected from the group consisting of Raman, UV/VIS, IR or x-ray spectroscopy.
	,,
1	16. A method according to claim 14, wherein the spectroscopic analysis is x-
2	ray spectroscopy.
1	17.—A method according to claim 1, wherein the microvolume is enclosed
/ 2	within a material defining the microvolume such that in a volume of the
~	

microvolume and the material defining the microvolume that an x-ray beam used

for x-ray spectroscopy of a crystal will traverse in the process of performing x-ray

5 spectroscopy on a crystal within the microvolume, the volume of the microvolume



- 6 contains at least as many electrons as the sum of the electrons contained in the
- 7 volume of the material defining the microvolume that the x-ray beam will traverse.
- 1 18. A method according to claim 1, wherein the microvolume is enclosed
- 2 within a material defining the microvolume such that in a volume of the
- 3 microvolume and the material defining the microvolume that an x-ray beam used
- 4 for x-ray spectroscopy of a crystal will traverse in the process of performing x-ray
- 5 spectroscopy on a crystal within the microvolume, the volume of the microvolume
- 6 contains at least three times as many electrons as the sum of the electrons
- 7 contained in the volume of the material defining the microvolume that the x-ray
- 8 beam will traverse.
- 1 19. A method according to claim 1, wherein the microvolume is enclosed
- within a material defining the microvolume such that in a volume of the
- 3 microvolume and the material defining the microvolume that an x-ray beam used
- 4 for x-ray spectroscopy of a crystal will traverse in the process of performing x-ray
- 5 spectroscopy on a crystal within the microvolume, the volume of the microvolume
- 6 contains at least five times as many electrons as the sum of the electrons contained
- 7 in the volume of the material defining the microvolume that the x-ray beam will
- 8 traverse.
- 1 20. A method according to claim 1, wherein the microvolume is enclosed
- 2 within a material defining the microvolume such that in a volume of the
- 3 microvolume and the material defining the microvolume that an x-ray beam used
- 4 for x-ray spectroscopy of a crystal will traverse in the process of performing x-ray
- 5 spectroscopy on a crystal within the microvolume, the volume of the microvolume
- 6 contains at least ten times as many electrons as the sum of the electrons contained
- 7 in the volume of the material defining the microvolume that the x-ray beam will
- 8 traverse.
- 1 21. A method according to claim 1, wherein material defining the microvolume
- 2 comprises a groove designed to reduce a number of electrons that an x-ray beam
- 3 used for x-ray spectroscopy of a crystal will traverse in the process of performing
- 4 x-ray spectroscopy on a crystal within the microvolume.

- 1 22. A method according to caim 1, wherein the method further comprises
- 2 delivering the plurality of different erystallization samples to the enclosed
- 3 microvolume.

17

- 1 A method according to claim 1, wherein the method further comprises 23.
- 2 forming the plurality of different crystallization samples within the enclosed
- 3 microvolume.

- 24. A method according to claim 1, wherein one or more dividers is positioned between the crystallization samples to separate the crystallization samples within the enclosed microvolume.
- 1 25. A method according to claim 1, wherein the divider is formed of an
- 2 . impermeable material.

- A method according to claim 25, wherein the impermeable material is an 26. impermeable liquid!
- A method according to claim 25, wherein the impermeable material is an 1 27.
- 2 impermeable solid.

1

- 28. A method according to claim 25, wherein the divider is formed of a permeable material.
- 29. A method according to claim 25, wherein the divider is formed of a
- 2 semipermeable material.

1


A method according to claim 29, wherein the semipermeable material is a

2 gas.

1

- A method according to claim 29, wherein the semipermeable material is a
- 2 liquid.

H:\PRIVATE\H&D\SYRRX\708\PATAPP-JUNE 8.DOC



actor